



OPTIMUM  
LUBRICANTS LIMITED

ISO 9001:2015 CERTIFIED



PRODUCT DATA SHEET (PDS)

# COMET SUMMER COOLANT

## DESCRIPTION

Comet Summer Coolant is a premium ready to use performance coolant and environmentally sensitive radiator coolant. The product is formulated with super concentrate which provides excellent corrosion protection and heat transfer properties to provide long term protection of the cooling systems of passenger cars, light trucks and heavy-duty diesel engines.

## FEATURES & BENEFITS

- The inhibitor system provides corrosion protection for all engines and cooling system metals including aluminum, iron, steel, copper and solder alloys.
- Low rate of depletion of the organic inhibitor ensures long-term corrosion protection under all conditions.
- Excellent inhibitor system protects wet liner from cavitation erosion, and provides exceptional protection to aluminum surfaces under heat transfer conditions.
- Prolonged water pump life due to fewer dissolved solids due to its excellent corrosion protection.

## APPLICATIONS

- Passenger car gasoline and diesel engines.
- Light duty commercial gasoline and diesel engine.
- Heavy duty diesel engines fitted with "wet" and "fry" liners.
- On and off-highway service trucks.
- High temperature aluminum engine blocks.

## MEETS PERFORMANCE LEVELS

- Mercedes Benz Sheet 325.0
- GM/ Opel B040 0240/QL 130 100
- SAAB 6901 599/ MAN 324/ BMW N 600 69.0
- MTU MTL 5048/ VW 774 C/ SABS 1251



Optimum Lubricants Ltd.  
ISO 9001:2015 CERTIFIED  
P.O. BOX 49925 - 00100

Phone: +254 725 872 425  
+254 726 706 398  
Email: [sales@cometoil.com](mailto:sales@cometoil.com)  
Website: [www.cometoil.com](http://www.cometoil.com)





OPTIMUM  
LUBRICANTS LIMITED

ISO 9001:2015 CERTIFIED



PRODUCT DATA SHEET (PDS)

# COMET SUMMER COOLANT

## PHYSICAL PROPERTIES

Properties	Method	Unit	Typical Values
Appearance	Visual		Clear & Bright
Color			Green
Boiling point	ASTM D 1120	°C	98
Density @ 15 °C	ASTM D 1298	Kg/l	1.625
Ph			7.6

## WARNING

The coolant contains super concentrate which is harmful or fatal if swallowed. Avoid both eye and skin contact. If accidentally swallowed, do not induce vomiting. Provide large quantities of water and immediately seek medical attention. If splashed in the eyes, wash with clean water for at least 15 minutes. In all cases, seek medical attention. Never give anything by mouth to an unconscious person.

## HEALTH AND SAFETY

Prolonged and repeated contact with oil may cause skin disorders. In case of skin contact wash immediately with soap and water. Do not discharge used oils in to drains or environment. Dispose to authorized used oil collection point.

*NB: Always store on temperatures between -5 to 40 °C*



Optimum Lubricants Ltd.  
ISO 9001:2015 CERTIFIED  
P.O. BOX 49925 - 00100

Phone: +254 725 872 425  
+254 726 706 398  
Email: sales@cometoil.com  
Website: www.cometoil.com

