



OPTIMUM
LUBRICANTS LIMITED

ISO 9001:2015 CERTIFIED



PRODUCT DATA SHEET (PDS)

COMET CVT

DESCRIPTION

Comet CVT Fluid is formulated with premium synthetic base stocks, long-life friction modifiers, special anti-wear additives, and shear stable viscosity modifiers. CVT Fluid is recommended for use in most belt and chain-driven continuously variable transmissions

FEATURES & BENEFITS

- Superior wet clutch performance
- Excellent anti-wear performance
- Excellent metal-metal friction protection
- Designed to provide excellent torque transfer

APPLICATIONS

Comet CVT is an essential component of the Continuously Variable Transmission, passenger cars for belt & chain cvts.

MEETS PERFORMANCE LEVELS

- JASO 1A
- Audi/VW (TL 52180; G 052 180; G 052 516)
- BMW/Mini Cooper 8322 0 136 376/8322 0 429 154 (EZL 799)
- Daihatsu (Amix CVTF-DC / Amix CVTF DFE)
- Dodge / Jeep CVT (NS-2 / CVTF+4/ MOPAR CVT 4)



Optimum Lubricants Ltd.
ISO 9001:2015 CERTIFIED
P.O. BOX 49925 - 00100

Phone: +254 725 872 425
+254 726 706 398

Email: sales@cometoil.com
Website: www.cometoil.com





OPTIMUM
LUBRICANTS LIMITED

ISO 9001:2015 CERTIFIED



PRODUCT DATA SHEET (PDS)

COMET CVT

PHYSICAL PROPERTIES

Properties	Test Method	Unit	Typical Values
Appearance	Visual		red
Kinematic Viscosity @ 40 OC	ASTM D 445	Cst	34.0
Kinematic Viscosity @ 100 OC	ASTM D 445	Cst	7.2
Viscosity Index	ASTM D 2270		183
Pour point	ASTM D 97	OC	-26
Flash point COC	ASTM D92	OC	200
Base number	ASTMD 2896		11.12
Pour point	ASTM D 97	OC	-28
Flash point COC	ASTM D92	OC	226

HEALTH AND SAFETY

Prolonged and repeated contact with oil may cause skin disorders. In case of skin contact, wash immediately with soap and water. Do not discharge used oils into drains or the environment. Dispose to an authorized used oil collection point.

NB: Always store on temperatures between -5 to 40 oc



Optimum Lubricants Ltd.
ISO 9001:2015 CERTIFIED
P.O. BOX 49925 - 00100

Phone: +254 725 872 425
+254 726 706 398
Email: sales@cometoil.com
Website: www.cometoil.com

