



OPTIMUM
LUBRICANTS LIMITED

ISO 9001:2015 CERTIFIED



PRODUCT DATA SHEET (PDS)

AUTOMOTIVE MULTI USE GREASE

DESCRIPTION

Comet Automotive Multiuse Grease is a high quality grease thickened with lithium soap and fortified with additives to improve oxidation characteristics, rust and corrosion prevention, and friction resistance.

Comet Automotive Multiuse Grease provides maximum protection by adhering well to the lubricated bearing surfaces sealing them from dirt and abrasive contaminations.

APPLICATIONS

- Wheel bearings.
- Plain and rollers bearing.
- Electrical motor bearing.
- Ideal for centralized lubricating systems operating at normal temperatures.

FEATURES & BENEFITS

- Performance at higher temperatures up to 180 degrees.
- Corrosion resistance.
- Oxidation and mechanical stability.
- Consistency during prolonged storage period.



Optimum Lubricants Ltd.
ISO 9001:2015 CERTIFIED
P.O. BOX 49925 - 00100

Phone: +254 725 872 425
+254 726 706 398
Email: sales@cometoil.com
Website: www.cometoil.com





OPTIMUM
LUBRICANTS LIMITED

ISO 9001:2015 CERTIFIED



PRODUCT DATA SHEET (PDS)

AUTOMOTIVE MULTI USE GREASE

Properties	Method	Unit	Typical Values	
Soap type			Lithium	
NLGI			2	3
Appearance	Visual		Red	Red
Unworked penetration@25 °C	ASTM D 217	mm	264	218
Worked 60 strokes @ 25 °C	ASTM D 217	mm	275	235
Drop point	ASTMD 2265		222	222

HEALTH AND SAFETY

Prolonged and repeated contact with oil may cause skin disorders .Incase of skin contact,wash immediately with soap and water. Do not discharge used oils in to drains or environment. Dispose to authorized used oil collection point.

NB: : Buckets and drums for greases should be stored upright and the surface of grease should be smothered to avoid separation always store on temperatures between -5 to 40 °C



Optimum Lubricants Ltd.
ISO 9001:2015 CERTIFIED
P.O. BOX 49925 - 00100

Phone: +254 725 872 425
+254 726 706 398
Email: sales@cometoil.com
Website: www.cometoil.com

