



OPTIMUM
LUBRICANTS LIMITED

ISO 9001:2015 CERTIFIED



PRODUCT DATA SHEET (PDS)

COMET SLIDEX 32, 68, 100 & 220

DESCRIPTION

Comet Slidex Oils are specially formulated for the lubrication of slide ways on machine tools as well as plastic slide ways. Comet Slidex Oils are fortified with additives to impart tackiness and adhesiveness. Comet Slidex overcomes stick-slip motion associated with slow moving parts. It can be used on all horizontal and vertical slide ways where a good quality lubricant is required for protection of the slide ways. Comet Slidex Oil protects slide ways against staining and corrosion.

APPLICATIONS

Comet Slidex Oil is recommended for all slideways to reduce frictions .

MEETS PERFORMANCE LEVEL

- DIN 51524/2 (HLP)
- DIN 51 502 CGLP
- LLC

FEATURES & BENEFITS

- It provides excellent lubricity .
- Provides excellent friction characteristics .

HEALTH AND SAFETY

Prolonged and repeated contact with oil may cause skin disorders .In case of skin contact, wash immediately with soap and water. Do not discharge used oils in to drains or environment. Dispose at authorized used oil collection point.

NB: Always store on temperatures between -5° C to 40° C



Optimum Lubricants Ltd.
ISO 9001:2015 CERTIFIED
P.O. BOX 49925 - 00100

Phone: +254 725 872 425
+254 726 706 398
Email: sales@cometoil.com
Website: www.cometoil.com





OPTIMUM
LUBRICANTS LIMITED

ISO 9001:2015 CERTIFIED



PRODUCT DATA SHEET (PDS)

COMET SLIDEX 32, 68, 100 & 220

PHYSICAL PROPERTIES

ISO VG	Method	units	32	68	100	220
Kinematic Viscosity @ 40 °C	ASTM D 445	Cst	32.2	68.0	102	220
Kinematic Viscosity @ 100 °C	ASTM D 445	Cst	5.52	8.8	11.56	20.0
Viscosity Index	ASTM D 2270		108	102	100	105
Density @ 15 °C	ASTM D 1298	Kg/l	0.865	0.880	0.889	0.892
Pour point	ASTM D 97	°C	-15	-15	-15	-15
Flash point COC	ASTM D92	°C	212	213	215	216



Optimum Lubricants Ltd.
ISO 9001:2015 CERTIFIED
P.O. BOX 49925 - 00100

Phone: +254 725 872 425
+254 726 706 398
Email: sales@cometoil.com
Website: www.cometoil.com

