



OPTIMUM
LUBRICANTS LIMITED

ISO 9001:2015 CERTIFIED



PRODUCT DATA SHEET (PDS)

COMET TWO STROKE

DESCRIPTION

Comet 2T is a high performance, two-stroke engine oil. It can be used in motorcycles and scooters.

APPLICATIONS

- Recommended for lubrication of two strokes engines where an API TC and JASO FB level performance is desired.

FEATURES & BENEFITS

- Specially formulated to avoid spark plug fouling.
- Thermal and oxidation stability.
- Protection against pre-ignition problems

MEETS PERFORMANCE LEVELS

Exceeds API TC
JASO FB



Optimum Lubricants Ltd.
ISO 9001:2015 CERTIFIED
P.O. BOX 49925 - 00100

Phone: +254 725 872 425
+254 726 706 398
Email: sales@cometoil.com
Website: www.cometoil.com





OPTIMUM
LUBRICANTS LIMITED

ISO 9001:2015 CERTIFIED



PRODUCT DATA SHEET (PDS)

COMET TWO STROKE

PHYSICAL PROPERTIES

Properties	Test Method	Unit	Typical Values
Appearance	Visual		Clear & Bright
SAE Grade			20
Kinematic Viscosity @ 40 °C	ASTM D 445	Cst	69
Kinematic Viscosity @ 100 °C	ASTM D 445	Cst	8.7
Viscosity Index	ASTM D 2270		97
Density @ 15 °C	ASTM D 1298	Kg/l	0.876
Pour point	ASTM D 97	°C	-13
Flash point COC	ASTM D92	°C	226

HEALTH AND SAFETY

Prolonged and repeated contact with oil may cause skin disorders. In case of skin contact, wash immediately with soap and water. Do not discharge used oils into drains or environment. Dispose to authorized used oil collection point.

NB: always store on temperatures between -5 to 40 °C



Optimum Lubricants Ltd.
ISO 9001:2015 CERTIFIED
P.O. BOX 49925 - 00100

Phone: +254 725 872 425
+254 726 706 398
Email: sales@cometoil.com
Website: www.cometoil.com

