



OPTIMUM
LUBRICANTS LIMITED

ISO 9001:2015 CERTIFIED



PRODUCT DATA SHEET (PDS)

COMET SYNTHETIC CHAIN SAW OIL

DESCRIPTION

Comet Synthetic Chain Saw Oil is formulated from synthesized base stock and fortified with additives to enhanced oxidation stability, reduce volatility and improve operating temperatures. Comet synthetic Chain Saw Oil has high viscosity index thus enabling it to function under high temperatures.

APPLICATIONS

Comet Synthetic Chain Saw Oil is used in equipment.

- Conveyor chain
- Dryers
- Heat setting and conditioning frames
- Oven chains

FEATURES & BENEFITS

- Stable at high chain temperatures
- Strong film thickness
- Stable to oxidation
- Superior antiwear and antirust properties



Optimum Lubricants Ltd.
ISO 9001:2015 CERTIFIED
P.O. BOX 49925 - 00100

Phone: +254 725 872 425
+254 726 706 398
Email: sales@cometoil.com
Website: www.cometoil.com





OPTIMUM
LUBRICANTS LIMITED

ISO 9001:2015 CERTIFIED



PRODUCT DATA SHEET (PDS)

COMET SYNTHETIC CHAIN SAW OIL

PHYSICAL PROPERTIES

Properties	Method	Unit	150
Appearance	Visual		Clear and bright
Kinematic Viscosity @ 40 °C	ASTM D 445	Cst	152
Kinematic Viscosity @ 100 °C	ASTM D 445	Cst	17
Viscosity Index	ASTM D 2270		121
Density @ 15 °C	ASTM D 1298	Kg/l	0.892
Pour point	ASTM D 97	°C	-11
Flash point COC	ASTM D92	°C	251

HEALTH AND SAFETY

Prolonged and repeated contact with oil may cause skin disorders .In case of skin contact, wash immediately with soap and water. Do not discharge used oils in to drains or environment. Dispose to authorized used oil collection point.

NB: Always store on temperatures between -5 to 40 °C



Optimum Lubricants Ltd.
ISO 9001:2015 CERTIFIED
P.O. BOX 49925 - 00100

Phone: +254 725 872 425
+254 726 706 398
Email: sales@cometoil.com
Website: www.cometoil.com

