



OPTIMUM
LUBRICANTS LIMITED
ISO 9001:2015 CERTIFIED



PRODUCT DATA SHEET (PDS)

COMET GUM GREASE

DESCRIPTION

Comet Gum Grease is a high quality grease, thickened with lithium with black viscous liquid and fortified with additives to impart oxidation, rust, corrosion, extreme pressure and friction resistance. Comet Gum Grease provides maximum protection by adhering well to the lubricated bearing surfaces sealing them from dirt and abrasive contaminations.

APPLICATIONS

- Recommended applications in high performance wheel bearings, chassis points and water pump bearings.

FEATURES & BENEFITS

- Resistance to water washout
- Excellent oxidation stability.
- Anti-Rust & Corrosion resistance

HEALTH AND SAFETY

Prolonged and repeated contact with grease may cause skin disorders. In case skin contact, wash immediately with soap and water. Do not discharge used oils in to drains or the environment. Dispose to an authorized used oil collection point.

NB: buckets and drums for greases should be stored upright and the surface of grease should be smothered to avoid separation always store on temperatures between -5 to 40 oc



Optimum Lubricants Ltd.
ISO 9001:2015 CERTIFIED
P.O. BOX 49925 - 00100

Phone: +254 725 872 425
+254 726 706 398
Email: sales@cometoil.com
Website: www.cometoil.com





OPTIMUM
LUBRICANTS LIMITED

ISO 9001:2015 CERTIFIED



PRODUCT DATA SHEET (PDS)

COMET GUM GREASE

PHYSICAL PROPERTIES

Properties	Test Method	Unit	Typical Values	
Soap type			Lithium	
Nlgi			2	3
Appearance	Visual		Black	black
Unworked penetration@25°C	ASTM D 217	mm	264	218
Worked 60 strokes @ 25 °C	ASTM D 217	mm	275	235
Drop point	ASTMD 2265		180	180



Optimum Lubricants Ltd.
ISO 9001:2015 CERTIFIED
P.O. BOX 49925 - 00100

Phone: +254 725 872 425
+254 726 706 398
Email: sales@cometoil.com
Website: www.cometoil.com

