



OPTIMUM
LUBRICANTS LIMITED

ISO 9001:2015 CERTIFIED



PRODUCT DATA SHEET (PDS)

COMET AUTOMATIC TRANSMISSION OIL

DESCRIPTION

Comet ATF is a multifunctional power transmission fluid designed for power shift transmission and power steering system applications. It is formulated for passenger cars and commercial vehicles automatic transmission. It can also be used for hydraulic system of mobile and off highway equipment where it is recommended.

MEETS PERFORMANCE LEVELS

- Allison C-4
- Dexron III
- Caterpillar TO-2

FEATURES & BENEFITS

- Provides extended fluid service life.
- Provide longer equipment life.
- The product is compatible with seal materials.
- The product provides fluidity over a wide range of temperature.

APPLICATIONS

- Power steering units.
- Automatic heavy-duty automatic machine.
- High-pressure hydraulic system.
- Torque converters where Allison C4 fluids are requested.
- Power shift transmission.



Optimum Lubricants Ltd.
ISO 9001:2015 CERTIFIED
P.O. BOX 49925 - 00100

Phone: +254 725 872 425
+254 726 706 398
Email: sales@cometoil.com
Website: www.cometoil.com





OPTIMUM
LUBRICANTS LIMITED

ISO 9001:2015 CERTIFIED



PRODUCT DATA SHEET (PDS)

COMET AUTOMATIC TRANSMISSION OIL

PHYSICAL PROPERTIES

Properties	Test Method	Unit	Typical Values
Appearance	Visual		red
Kinematic Viscosity @ 40 °C	ASTM D 445	Cst	32.72
Kinematic Viscosity @ 100 °C	ASTM D 445	Cst	7.06
Viscosity Index	ASTM D 2270		186
Density @ 15°C	ASTM D 1298	Kg/l	0.855
Pour point	ASTM D 97	°C	-47
Flash point COC	ASTM D92	°C	232

HEALTH AND SAFETY

Prolonged and repeated contact with oil may cause skin disorders. In case of skin contact, wash immediately with soap and water. Do not discharge used oils into drains or environment. Dispose to authorized used oil collection point.

NB: Always store on temperature between -5° C to 40° C



Optimum Lubricants Ltd.
ISO 9001:2015 CERTIFIED
P.O. BOX 49925 - 00100

Phone: +254 725 872 425
+254 726 706 398
Email: sales@cometoil.com
Website: www.cometoil.com

