



OPTIMUM  
LUBRICANTS LIMITED

ISO 9001:2015 CERTIFIED



PRODUCT DATA SHEET (PDS)

# COMET SYNTON 15W/40

## DESCRIPTION

Comet Synton 15W40 CI-4 /SL is a multigrade engine oil, formulated from synthetic base oil and advanced additive technology designed to meet the requirements of modern wide range of diesel and gasoline engines requiring an API CI-4, API SL quality oil.

Comet Synton 15W40 CI-4/SL helps extend engine life in the most demanding on and off road conditions. The advanced formulation offers exceptional performance in new high output engines, including those with Exhaust Gas Recirculation (EGR).

## APPLICATIONS

- Designed for use in severe conditions for high speed, four stroke both naturally aspirated, turbo charged diesel engines.
- Suitable for the latest electronically controlled diesel engines fitted with EGR and SCR exhaust after treatment systems.
- Used for mixed fleets of both diesel and gasoline engines.
- Commercial road transport.
- Off-highway vehicles and plant.
- Agricultural tractors and farm machinery.

## FEATURES & BENEFITS

- Resistance to oil thickening and protection against filter plugging results in extended oil drain intervals
- Excellent upper ring-belt deposit control under high temperatures encountered in turbocharged diesel engines.
- Outstanding oxidation stability and soot control capability
- Advanced additive technology optimizes soot dispersion, deposit control and wear protection
- Maximized engine life due to outstanding wear protection in valve train and component scuffing under high loads.
- Engine fuel economy and reduced oil consumption.

## MEETS PERFORMANCE LEVELS

API CI-4/SL, ACEA: E7/E5/E3/B4/B3/A3, MB228.3, VOLVO VDS-3, RENAULT RLD, MAN M3275, MACK EO-M Plus, MTU Type 2 Quality, CUMMINS CES 20078/77/76, CATERPILLAR ECF-1, and GLOBAL DHD-1



Optimum Lubricants Ltd.  
ISO 9001:2015 CERTIFIED  
P.O. BOX 49925 - 00100

Phone: +254 725 872 425  
+254 726 706 398  
Email: sales@cometoil.com  
Website: www.cometoil.com





OPTIMUM  
LUBRICANTS LIMITED

ISO 9001:2015 CERTIFIED



PRODUCT DATA SHEET (PDS)

# COMET SYNTON 15W/40

## PHYSICAL PROPERTIES

Properties	Test Method	Unit	Typical Values
Appearance	Visual		Clear & Bright
SAE Grade			15W 40
Kinematic Viscosity @ 40 °C	ASTM D 445	Cst	112.7
Kinematic Viscosity @ 100 °C	ASTM D 445	Cst	14.6
Viscosity Index	ASTM D 2270		133
Density @ 15 °C	ASTM D 1298	Kg/l	0.885
Base number	ASTMD 2896		11.12
Pour point	ASTM D 97	°C	-28
Flash point COC	ASTM D92	°C	226

## HEALTH AND SAFETY

Prolonged and repeated contact with oil may cause skin disorders. In case of skin contact, wash immediately with soap and water. Do not discharge used oils in to drains or the environment. Dispose to an authorized used oil collection point.



Optimum Lubricants Ltd.  
ISO 9001:2015 CERTIFIED  
P.O. BOX 49925 - 00100

Phone: +254 725 872 425  
+254 726 706 398  
Email: [sales@cometoil.com](mailto:sales@cometoil.com)  
Website: [www.cometoil.com](http://www.cometoil.com)

