



OPTIMUM
LUBRICANTS LIMITED

ISO 9001:2015 CERTIFIED



PRODUCT DATA SHEET (PDS)

WATER RESISTANCE GREASE

DESCRIPTION

Comet Water Resistance Grease is high quality water resistance grease, thickened with calcium complex soap and fortified with additives to impart oxidation, rust, corrosion, extreme pressure and friction resistance. Comet Water Resistance Grease provides maximum protection by adhering well to the lubricated bearing surfaces sealing them from dirt and abrasive contaminations.

APPLICATIONS

- Recommended applications in high performance wheel bearings
- Chassis points and water pump bearings.
- Lubricating machinery operating in damp conditions.

FEATURES & BENEFITS

- Resistance to water washout
- Long service life through excellent oxidation stability.
- Anti-Rust & Corrosion Additives
- Performance additives to enhance the life & performance of the grease.



Optimum Lubricants Ltd.
ISO 9001:2015 CERTIFIED
P.O. BOX 49925 - 00100

Phone: +254 725 872 425
+254 726 706 398
Email: sales@cometoil.com
Website: www.cometoil.com





OPTIMUM
LUBRICANTS LIMITED

ISO 9001:2015 CERTIFIED



PRODUCT DATA SHEET (PDS)

WATER RESISTANCE GREASE

PHYSICAL PROPERTIES

Properties	Test Method	Unit	Typical values	
Soap type			Calcium complex	
NIgi			2	3
Appearance	Visual		Beige	Beige
Unworked penetration@25 °C	ASTM D 217	mm	264	218
Worked 60 strokes @ 25 °C	ASTM D 217	mm	275	235
Drop point	ASTMD 2265		280	280

HEALTH AND SAFETY

Prolonged and repeated contact with oil may cause skin disorders .Incase of skin contact, wash immediately with soap and water. Do not discharge used oils in to drains or environment. Dispose to authorized used oil collection point.

NB: buckets and drums for greases should be stored upright and the surface of grease should be smothered to avoid separation always store on temperatures between -5 to 40 °C



Optimum Lubricants Ltd.
ISO 9001:2015 CERTIFIED
P.O. BOX 49925 - 00100

Phone: +254 725 872 425
+254 726 706 398
Email: sales@cometoil.com
Website: www.cometoil.com

