



OPTIMUM
LUBRICANTS LIMITED

ISO 9001:2015 CERTIFIED



PRODUCT DATA SHEET (PDS)

COMEX PLUS 15W40

DESCRIPTION

Comex Plus SAE 15W40 is a multigrade mineral lubricant for on-road diesel engines, heavy-duty diesel engine oil that provides shear stability under wide variety of severe service conditions. Comex Plus 15W40 is developed for all diesel engines, turbocharged or not, in severe service conditions in all seasons.

APPLICATIONS

- Designed for use in severe conditions for high speed, four stroke both naturally aspirated & turbo charged diesel engines.
- Mixed fleet diesel engines (high speed, four stroke, naturally aspirated or turbo charged).
- Mixed fleets of both diesel and gasoline engines.
- Commercial road transport.

FEATURES & BENEFITS

- Stability in viscosity, guaranteeing efficient engine lubrication in severe conditions.
- Maintains upper ring-belt deposit control under high temperature encountered in turbocharged diesel engines.
- Outstanding detergent, dispersant and anti-wear properties keep the engine clean and enable effective control of soot, sludge and piston deposits.
- Maximized engine life due to outstanding wear protection in valve train and component scuffing under high loads.
- Engine fuel economy and reduced oil consumption.

MEETS PERFORMANCE LEVELS

API CF-4/SJ, MIL 2104E, MB228.1, ALLISON C-4, VOLVO VDS, MAN 271, VOLVO VDS, CAT TO-2



Optimum Lubricants Ltd.
ISO 9001:2015 CERTIFIED
P.O. BOX 49925 - 00100

Phone: +254 725 872 425
+254 726 706 398
Email: sales@cometoil.com
Website: www.cometoil.com





OPTIMUM
LUBRICANTS LIMITED

ISO 9001:2015 CERTIFIED



PRODUCT DATA SHEET (PDS)

COMEXPLUS 15W40

PHYSICAL PROPERTIES

Properties	Test Method	Unit	Typical Values
Appearance	Visual		Clear & Bright
SAE Grade			15W 40
Kinematic Viscosity @ 40 °C	ASTM D 445	Cst	113.4
Kinematic Viscosity @ 100 °C	ASTM D 445	Cst	14.82
Viscosity Index	ASTM D 2270		135
Density @ 15 °C	ASTM D 1298	Kg/l	0.885
Base number	ASTMD 2896		11.12
Pour point	ASTM D 97	°C	-23
Flash point COC	ASTM D92	°C	232

HEALTH AND SAFETY

Prolonged and repeated contact with oil may cause skin disorders .Incase of skin contact,wash immediately with soap and water. Do not discharge used oils in to drains or environment. Dispose to authorized used oil collection point.

NB: always store on temperatures between -5 to 40°C



Optimum Lubricants Ltd.
ISO 9001:2015 CERTIFIED
P.O. BOX 49925 - 00100

Phone: +254 725 872 425
+254 726 706 398
Email: sales@cometoil.com
Website: www.cometoil.com

