



OPTIMUM
LUBRICANTS LIMITED

ISO 9001:2015 CERTIFIED



PRODUCT DATA SHEET (PDS)

AGROCOMET 10W/30

DESCRIPTION

Comet Agrocomet SAE 20W40 is an extra performance, heavy-duty engine, hydraulic oil and transmission oil for various types of agriculture equipment including the tractors. This is very specialized oil, which has been formulated to meet the most stringent requirements of agriculture sector.

MEETS PERFORMANCE LEVELS

Meets API CG-4, ACEA E3 and Exceeds API CF-4/ GL-4, John Deere J20C, Massery Ferguson MII39, FORD M2C-159A,B,C, Eaton :M2950S, TO-2

FEATURES & BENEFITS

- Multifunctional: Single lubricant for the majority of agricultural (farm) applications.
- Thermal Stability: Resistant to oil degradation and the formation of sludge at high operating temperatures.
- Gear Protection: Effective load carrying capability in transmission, gears and bearings giving long life and reliable performance.
- Wet Brake and power take-off control: Excellent friction characteristics to minimize noise and maximize efficiency.

APPLICATIONS

- Oil immersed brakes.
- Tractor hydraulic systems.
- Tractor power take-off systems.
- Power steering units.
- Hydrostatic transmissions.
- Gears drive units.



Optimum Lubricants Ltd.
ISO 9001:2015 CERTIFIED
P.O. BOX 49925 - 00100

Phone: +254 725 872 425
+254 726 706 398
Email: sales@cometoil.com
Website: www.cometoil.com



PRODUCT DATA SHEET (PDS)

AGROCOMET 10W/30

PHYSICAL PROPERTIES

Properties	Test Method	Unit	Typical Values
Appearance	Visual		Clear & Bright
SAE Grade			10 W 30
Kinematic Viscosity @ 40 OC	ASTM D 445	Cst	119.52
Kinematic Viscosity @ 100 OC	ASTM D 445	Cst	13.95
Viscosity Index	ASTM D 2270		115
Density @ 15 OC	ASTM D 1298	Kg/l	0.885
Base number	ASTMD 2896		11.12
Pour point	ASTM D 97	OC	-28
Flash point COC	ASTM D92	OC	226

HEALTH AND SAFETY

Prolonged and repeated contact with oil may cause skin disorders. In case of skin contact, wash immediately with soap and water. Do not discharge used oils into drains or environment. Dispose to authorized used oil collection point.

NB: Always store on temperature between -5° C to 40° C

